

















AHD CAMERA SERIES

4IN1SYSTEM AHD/TVI/CVI/CVBS



























- 1/2.8" progressive CMOS scan
- Video System 4-in-1 (AHD/TVI/CVI/CVBS)
- 1920x1080P Megapixel
- Day / Night EXT (ICR)/AUTO/Color/B/W
- DC Lens Support
- BNC Video Output x1 (BNC female)
- Power Supply x1 (DC jack female)
- OSD Button Support
- UTC/COC Control Support
- Power 12V DC +- 10%

Model	HA-304S20ST
Image Sensor	1/2.8" progressive CMOS scan
DSP	Nextchip NVP2441H
Pixels	1920x1080P Megapixel
Min. Illumination	Color: 0.0001Lux@(F1.2,AGC ON)
	B/W: OLUX with IR
Shutter Speed	Auto/manual (1/25s-1/100,000)
Day / Night	EXT (ICR)/AUTO/Color/B/W
S/N Ratio	52dB.
Gain Control	Support
OSD Menu	Support (auto close)
AWB	Support
AGC	Support
Sens-Up	Support
Image Brightness Adjust	Support
DWDR	Support
Defog	Support
Backlight Compensation	BLC/HSBLC
White Balance	ATW/AWC/indoor/outdoor/manual/AWB
2DNR	Support
3DNR	Support
Special	Cam title,D-effect, motion, privacy
GAMMA	Support
Image Sharpness Adjust	Support
Image Saturation Adjust	Support
mago outaration rajust	Capport
LSC	Support
LSC Lens	Support
Lens	Support CS
15.10*0.0	CS
Lens Mount Type	
Lens Mount Type DC Lens	CS Support
Lens Mount Type DC Lens Video Video Format	CS Support PAL(50Hz)/NTSC(60Hz)
Lens Mount Type DC Lens Video Video Format Video System	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS)
Lens Mount Type DC Lens Video Video Format	CS Support PAL(50Hz)/NTSC(60Hz)
Lens Mount Type DC Lens Video Video Format Video System Image Resolution	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female)
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female)
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female)
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support x1
Lens Mount Type DC Lens Video Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support x1 -3dC ~ +6dC, RH95 Max.
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max.
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support x1 -3dC ~ +6dC, RH95 Max.
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level Electrical	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max. ESD 5000 Volt
Lens Mount Type DC Lens Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level Electrical Power	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max. ESD 5000 Volt
Lens Mount Type DC Lens Video Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level Electrical Power Power Consumption	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max. ESD 5000 Volt
Lens Mount Type DC Lens Video Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level Electrical Power Power Consumption Mechanical	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max. ESD 5000 Volt
Lens Mount Type DC Lens Video Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level Electrical Power Power Consumption Mechanical Weight	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max. ESD 5000 Volt 12V DC +-10% 21mA/0.9W 0.7KG
Lens Mount Type DC Lens Video Video Video Format Video System Image Resolution Interfaces BNC Video Output Power Supply OSD Button UTC/COC Control LED Indicator Environmental Operating Temperature Storange Temperature Surge Protection Level Electrical Power Power Consumption Mechanical	CS Support PAL(50Hz)/NTSC(60Hz) 4-in-1 (AHD/TVI/CVI/CVBS) AHD/TVI/CVI 1080P@25/30fps CVBS@PAL/NTSC x1 (BNC female) x1 (DC jack female) Support Support Support x1 -3dC ~ +6dC, RH95 Max2dC ~ +6dC, RH95 Max. ESD 5000 Volt 12V DC +-10% 21mA/0.9W

AHD CAMERA SERIES

4IN1SYSTEM AHD/TVI/CVI/CVBS

