



HD NVR KIT

WIFI SURVEILLANCE SYSTEM





Feature

- With built-in dedicated WIFI module, for safer and more reliable transmission.
- Unpack and play when the power on, without configuration for live video.
- HD image quality, clear and delicate pictures.
- Special WIFI module for long distance transmission and strong anti-tamper ability.
- Capable for using with cable and without cable, adaptable for various environments
- Support P2P Cloud, remote connection in seconds, fluent image quality
- Multiple client softwares, support android / iOS / PC, etc.



HD NVR KIT

WIFI SURVEILLANCE SYSTEM

Wireless NVR Specification

Model	HW-3308 (X1)
Video input	8ch D1 / 960H / 720P / 960P / 1080P
HDMI Output	1ch, Resolution: 1024x768, 1280x1024, 1366x768, 1440x900, 1920x1080
VGA Output	1ch, Resolution: 1024x768, 1280x1024, 1366x768, 1440x900, 1920x1080
Resolution	D1 / 960H / 720P / 960P / 1080P
Playback	4ch / Network Playback 1,4,9ch.
Recording	Manual, time, motion detection, alarm
Storage	1 SATA
Storage capacity	6TB for each HDD
Network interface	1 RJ45 10M/100M, 2 WIFI connector
USB interface	2 USB2.0
Power consumption	≤5W
Power	DC12V
working temperature	-10℃---+55℃
Dimension (mm)	258*210*42mm
Working humidity	10%--90%RH





Key Fetures

- 1/3" Progressive Scan Sensor
- Resolution 1280x960P (1.3MP) / H.264
- Fixed Iris Manual Lens 4.0mm.
- IP66
- Support APP IPPro (Cloud ID)
- Support Browsers (IE)
- Support CMS (EseeCloud)
- Support Image Setup
- Support Flip, Mirror
- Support Build-in Repeater Wi-Fi
- Support DDNS
- Support PPOE
- Support User Management
- Support NTP (Time Sync.)
- Support Network Upgrade Software




HD NVR KIT

WIFI SURVEILANCE SYSTEM

Specification

Model	HW-33B13ST (X1)
Image Sensor	1/3" Progressive Scan Sensor
Video Compression	H.264 / MJPEG
Resolution	1280x960P
Stream Type	Support Dual Stream
Video Streaming	Main Stream 1280x960@15fps Second Stream 640x360@25fps
Bit Rate Control	CBR / VBR
Profile	Main / Baseline
S/N Ratio	>39.1 dB.
Signal System	PAL / NTSC
Min. Illumination	0.001 Lux
Shutter Speed	1/100s -1/120s
Lens Type	Fixed Iris Lens 4.0mm.
Day&Night	Color Only
Level of Protection	IP66
Anti-Thunder Level	Standard IEC61000-4-5
Interface	Network port x1 (RJ45) Water-Proof Wi-Fi 802.11b/g/n / Power input x1 (DC Jack)
Power Input	DC12V+-10% / Support POE (Class 0)
Power Consumption	<6W.
Working Temperature	-10C~+50C/30%~80% RH
Storage Temperature	-20C~+60C/20%~90% RH
Case Material	Aluminum Build-in Bracket
Weight	500g
Dimension	Φ66x180mm.





HD NVR KIT

WIFI SURVEILANCE SYSTEM

WIFI Camera Specification

Model	HW-33B13 (X7)
Sensor	1/3" Progressive Scan Sensor
Signal System	PAL/NTSC
Resolution	1280 x 960 4:3 High Definition
Minimum illumination	Color: 0.1 Lux; B/W: 0.01 Lux
Shutter	1/25s to 1/25,000s
Lens	4/6mm
OSD	Date Time & Title
White Balance	Auto
Day&Night	Auto / Color / BW
3D-DNR	Auto
Mirror / Flip	On / Off
smart stream	Dual-stream:1280x960@15fps, 640x360@15fps
S/N	> 39.1 Db
Interface	RJ45 / WIFI 802.11b/g/n
Anti-thunder Level	Standard IEC61000-4-5
Level of Protection	IP66
Working Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
Working Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Power Input	DC12V-1A
Power consumption	≤6W
Size	66*180mm
Weight	500g

Feature

- With built-in dedicated WIFI module,for safer and more reliable transmission.
- Unpack and play when the power on, without configuration for live video.
- HD image quality, clear and delicate pictures.
- Special WIFI module for long distance transmission and strong anti-tamper ability.
- Capable for using with cable and without cable,adaptable for various environments
- Support P2P Cloud, remote connection in seconds, fluent image quality
- Mutiple client softwares, support android / iOS / PC,etc.

