





NVR Wi-Fi Kit 4ch H.264 Full HD 1080P

- Support Build-in WIFI module with high-performance
- Support Automatically connection between NVR and IPC
- Support Video preview/recording/ playback/backup
- Support the mixed use of wireless and wire
- Support Auto matching, Intelligent add
- Support Auto bitrate
- Support Multi network segment
- Support Wi-Fi channel set up
- Support PC online remote, CMS
- Support Web online www.e-seenet.com
- Support SEQ
- Support Free DDNS hiview.org
- Support log
- Support User management
- Support Upgrade system
- Support Auto Maintenance
- Support IPC Maintenance
- Support Fast Network



Application
IP PRO

Specification

Model	HW-3304KIT20ST
Video Compression	Standard H.264 High profile
Video Input	4Ch
Resolution	1080P
Video System	PAL/NTSC
Auto Add	Support auto add ipc
Live View	
Split Screen	x1, x4 layout
HDMI resolution output	1080P@60Hz, 1080P@50Hz, 1440x900 1366x768, 1280x1024, 1024x768
OSD Alpha	Support
Auto Switch	Support
E-Zoom	Support live view/playback mode
Color Adjust	Support
Recording	
Over write	Support (Auto/Custom)
Record Plan	Time, Motion, Manual
Main Stream	1920x1080@15fps, Bitrate 3Mbps.
Sub Stream	640x360@15fps, Bitrate 256 Kbps.
Video Compression	H.264
Bitrate Control	VBR/CBR
Image Quiality Control	Adjustable
Back Up	U-Disk (AVI format)
Playback	
Local Playback layout	x1, x4 layout
Serach Mode	Time, Motion, Manual, Alarm
Network	
Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, 3G, FTP, Email
DDNS Provider	Hiview, Dyn dns, 3322, Change ip, NO-IP, Oray, NVR163
Wireless Standard	WiFi 802.11b/g/n
Application	iOS / Android (Ip pro)
User Interface	Browsers (IE), CMS, App
Onvif	Support Onvif 2.4
Alarm	
Buzzer	Support
system Alarm	HDD error, Insufficient disk space Network loss, IP conflict, Recodr error
Alarm Triggering	Buzzer, Email Notice (Max. 2 receiver) App notice
Interfaces	
HDMI	x1 (Max. 1080P)
VGA	x1
SATA	x1 (Max. 6Tb.)
USB 2.0	x2
Wi-Fi Antena	x2
RJ45	x1 (10M/100M)
Environmental	
Operating Temperature	-10C~+55C
Operating Humidity	10%-90%RH
Electrical	
Power	DC12V
Power Consumption	<5W.
Mechanic	
Case Material	Metal case
Dimension	258x210x42mm.

FULL HD
1080p



**FULL HD
1080p**

4



1080p

Wi-Fi

HDMI

CLOUD

P2P

IPC Wi-Fi Full HD 1080P

- 1/2.7" Image CMOS Sensor
- Resolution 1080P
- Frame rate 15fps
- H.264 video compression
- Fixed lens 4.0mm
- IR Array 4 Pcs./IR Distane 20-30M.
- Day&Night (IR CUT)
- Wifi antenna (802.11b/g/n)
- Wire connection (LAN)
- Onvif, WDR, ATW, 3D-DNR, IP66, Motion detect
- Power supply DC12V/1A
- Support Cloud P2P
- Support Web online www.e-seenet.com
- Support Mobile viewing iOS/Android (IP Pro)
- Support PC online remote, CMS
- Support HW-E4
- Support Wi-Fi repeater mode
- Support the mixed use of wireless and wire



Specification

Model	HW-33B20ST
Image Sensor	1/2.7" CMOS Sensor
Resolution	1920x1080P
Lens	Fixed lens 4.0mm.(M12)
Minimum illumination	Color: 0.1 Lux; B/W: 0.01 Lux
Shutter	1/25s to 1/25,000s
IR LED	IR Array 4 Pcs.
IR Distance	20-30M.
Day&Night	IR-CUT (Auto / Color / BW)
Video	
Video Compression	Standard H.264 High profile
Video System	PAL / NTSC
Stream	Support Dual stream
Main Stream	1920x1080@15fps, Bitrate 3Mbps.
Sub Stream	640x360@15fps, Bitrate 256 Kbps.
Bitrate Control	VBR / CBR
Image Quiality Control	Adjustable
Color Adjust	Support
White Balance	Auto
WDR	Support
3D-DNR	Support
Mirror / Flip	On / Off
Provacy Mask	Support
OSD	Support
S/N Ratio	> 39.1 Db
Network	
Protocol	TCP/IP, DHCP, DNS, DDNS, NTP, UPNP, NTP
Wireless Standard	WiFi 802.11b/g/n
WiFi Mode	Station mode, Access point mode, Repeater mode
User Interface	Browsers (IE), CMS, App
Onvif	Support Onvif 2.4
Application	iOS / Android (Ip pro)
Alarm	
Motion Detection	Support
Interfaces	
Wi-fi Antenna	x1 (WiFi 802.11b/g/n)
RJ45	x1 (10M/100M)
Environmental	
Level of Protection	IP66
Anti-Thunder Level	Standard IEC61000-4-5
Operating Temperature	-10℃~+50℃/30%~80% RH
Electrical	
Power	DC12V/1A
Power Consumption	< 6W.
Mechanic	
Case Material	Metal case
Weight	500g.
Dimension	66x180mm.



**Application
IP PRO**