

## N-IP322MB-P

### Main Features

- 1) Include HD 3.0 Mega pixel 3.6mm lens, with IR-Cut
- 2) 24pcs  $\Phi$ 5mm LED, IR distance: 20m
- 3) Metal Dome IP camera
- 4) 2.0MP/1080P real time. Main Stream : 1920\*1080@30FPS, Sub Stream: 704\*576@30FPS
- 5) with POE
- 6) Support Multi-Screen software and CMS (64CH at the same time)
- 7) Support Android, Iphone, Windows, Blackberry, Symbian mobile phone view



### Specification

	Model	N-IP322MB-P
Camera	Image Sensor	2.0 Mega pixels, 1/2.8" CMOS Sensor
	Effective Pixels	2.0MP/1080P: 1920*1080
	Scanning System	Progressive
	Electronic Shutter Speed	1/25~1/100,000 sec
	Min. Illumination	0.6Lux/F1.2(color),0.08Lux/F1.2(B/W) (0 Lux when IR ON)
	S/N Ratio	>50dB
Lens	Focal Length	HD 3.0 Mega pixel 3.6mm lens
Camera Features	IR Distance	24pcs $\Phi$ 5mm LED, IR distance: 20m
	IR Cut	Yes, with IR cut
	Wide Dynamic Range (WDR)	No
	Day/Night	Auto(ICR)/Color/B/W
	Backlight Compensation (BLC)	Auto
	White Balance	Auto
	Gain Control	Auto
	Noise Reduction	Yes
	Motion Detection	Yes
	Privacy Masking	Yes
Video	Compression	H.264 / AVI format
	Main Stream	1080P: 1920*1080@30FPS, 720P: 1280*720@30FPS, 1~30FPS adjustable
	Sub Stream	D1: 704*576@30FPS, 1~30FPS adjustable
	Bit Rate	CBR and VBR, 0,1M~6Mbps
Network	Ethernet	RJ-45 (10/100Base-T)
	Protocol	RTSP/Email/ARSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/DAS/IP authority
	ONVIF	Support latest ONVIF
	Max. User Access	5 users
	Smart Phone	iPhone, Android, Windows Mobile, BlackBerry, Symbian
Audio	Audio Input	N/A
	Audio output	N/A
	Audio Process	N/A
Auxiliary Interface	Memory Slot	N/A
	Alarm Input	N/A
	Alarm Output	N/A
	Alarm Function	Motion detection Center warning and picture pop-up linkage supported (after motion detection)
General	Operation function	Support WEB configuration; OSD; Real-Time Video transmission; Motion detection, Snap, CMS, VMEYE Applications, SDK
	Power Supply	DC12V
	Power Consumption	<5W
	Working Environment	-10°C~+60°C, 10%~90%

\*\*This specification is subject to change without notice.