

2.0 Mega pixel Motorized lens IP Camera with 30m IR

คุณภาพคุ้มค่า ตอบทุกความต้องการ

N-IP1023MB-W

Main Features

- 1/2.5" 2.0 Megapixel Progressive Scan Aptina CMOS sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps @ 1080P (1920×1080)
- Support DC12V power supply, PoE IEEE802.3af
- Lens : 2.8-12mm motorized lens
- 4 pcs Φ11 IR lights, Max. IR Distance: 30m
- WDR, Auto Back Focus, ROI function, Built-in Web server, NVR, CMS
- True Day/Night ICR, IP66 all-environments protection, Micro SD Card



Specification

	Model	N-IP1023MB-W
Camera	Image Sensor	1/2.5 " 2.0 Megapixel Progressive Scan A CMOS Sensor
	Effective Pixels	1920(H)×1080(V)
	Electronic Shutter	1/5s to 1/50,000s
	Mini. Illumination	Color:0.2Lux/F1.2 ;B/W:0.01Lux/F1.2;0Lux/F1.2(IR on)
	Signal Noise Ratio	>50dB
	Day/Night Mode	Auto, dual IR-Cut filter
	Gain Control	Auto/Manual
	White Balance	Auto/Manual
	WDR Dynamic Range	DWDR
	Lens	2.8-12mm motorized lens
	Max IR Distance	30m, 4 pcs Φ11 IR lights
Video	Video Compression	H.264/MJPEG Optional
	H.264 Encode Type	H.264 Baseline/H.264 Main Profile/H.264 High Profile Optional
	Video Bit Rate	Main Stream:500Kbps~12Mbps, Sub Stream:100Kbps~6Mbps
	Image Resolution	1080P(1920×1020) / 720P(1280×720) / D1(704×576/704×480)
	Encoding Speed	Main Stream: 1080P/720P (1~25fps/30fps), Extra Stream: D1/CIF(1~25fps/30fps)
Audio	Video Format	PAL/NTSC
	Audio Compression	G.711a/G.711u Optional
	Audio Bit Rate	G.711a(8kbps)/G.711u(8kbps)/
	Audio Input	1-channel 3.5mm audio interface MIC IN/Line IN
Network	Audio Output	1-channel 3.5mm audio interface (line level,600Ω)
	Ethernet	RJ-45 (10/100Base-T)
	Network Protocol	Ipv4/Ipv6,RTSP,TCP/UDP,HTTP,DHCP,DNS,FTP,DDNS,PPPoE,SMTP
	Common Features	One button Reset, Prevent Flicker, Dual-stream, Heartbeat, Password Protect, Video cover, Motion Alarm
	ONVIF	ONVIF Ver.2.3
	Max User Access	10 users
	Smart phone	Iphone , Ipad ,Android,
Auxiliary Interface	Remote Operation	Monitor, System setting, , Log information, Maintenance & Upgrade
	Reset Input	One Reset Button(Hold on 3 seconds at least)
	RS485	PTZ Control
	Memory Slot	Micro SD Card, Max 32GB
	Alarm Input	1-channel input, Normally Open/Normally Close modes adjustable
	Alarm Output	1-channel output,, 120VAC 1A/24VDC 1A
Environmental	Video Output	1Vp-p Composite Output(75Ω/BNC)
	Power Supply	DC12V
	Power Consumption	<10W
	Working Environment	-40°C ~ +60°C, Humidity less than95%(Non-condensing)
	Dimensions(mm)	248.8mm x 73.5mm
Weight(kg)	0.866Kg	

**This specification is subject to change without notice.