

N-N416L

Main Features

- 16CH H.264 NVR
- 16CH **960P** real time recording
- 16CH 960P Input, No alarm, No RS485
- with Network function, free DDNS, Cloud service, P2P function, Support all kinds of mobile view
- No USB 3G & USB WiFi
- Support VGA & HDMI simultaneously output
- Support 2pcs of HDD, Max. 4TB



Specification

| | Model | N-N416L |
|---------------------|----------------------|---|
| System | Main processor | Technical grade embedded microprocessor |
| | Operating system | Embedded LINUX operating system |
| | System resource | Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up. |
| Interface | Operation interface | 16 bit real color GUI interface support mouse operation |
| | Display screen | 1/4/9/16 screen |
| | Image encode | H.264 (High Profile) |
| | Monitor quality | Monitor: D1; VGA, HDMI |
| | Playback quality | 960P/720P/D1 |
| | Recording capability | 16ch 960P real-time |
| | Recording Frame Rate | PAL 100fps, NTSC 120fps |
| | Image Control | 6 Options |
| Audio | Motion detection | 192(16*12) detection area; multiple sensitivity |
| | Audio compression | G711A |
| Record Mode | Bidirectional talk | support |
| | Record mode | manual>alarm>motion detection>timing |
| Storage and back up | Video search | Time, date, event, channel search |
| | Space occupation | Video: CIF 4~5G/day*channel, D1 8~10G/day*channel; 960H 12G~20G/day*channel, 720P 20~30G/day*channel, Audio: 691.2M/day*channel |
| | Video storage | Local HDD, Network |
| | Back up mode | Network backup, USB portable HDD, USB imprint, SATA imprint |
| Interface | Video input | 16ch 960P |
| | Video output | 1ch VGA, 1ch HDMI |
| | Loop output | No |
| | Audio input | N/A |
| | Audio output | N/A |
| | Alarm input | N/A |
| | Alarm output | N/A |
| | Network port | RJ45 10M/100M self-adaptive Ethernet port |
| | PTZ control | RS485 |
| | USB port | 2*USB2.0 |
| | HDD port | 2 SATA ports(max to 4T each) |
| | Wireless port | No 3G, WIFI |
| Other | Power | 12V/2A |
| | Consumption | <10W(not including HDD) |
| | Temperature | 0°C - +55°C |
| | Humidity | 10% - 90% |
| | Atmosphere pressure | 86kpa - 106kpa |
| | Dimension | L233*W300*H45 mm |

**This specification is subject to change without notice.