hi-view®
High Resolution High Technology

HA-394BP202

2M Pixel | 180° Pan Rotation | 55° TiLT Rotation | 4X Optical Zoom | SMD LED Smart IR | DAY & Night Support | Digital WDR Support | BLC Support

MINI PTZ

PTZ CAMERA SERIES
4in1 System

hi-view®
High Resolution High Technology

HA-394BP202

2M Pixel | 180° Pan Rotation | 55° Tilt Rotation | 4X Optical Zoom | SMD LED Smart IR | DAY & Night Support | Digital WDR Support | BLC Support

Feature

- 1/2.8" SONY IMX 323 CMOS
- 4-in-1 (AHD/CVI/TVI/CVBS)
- lens 2.8-12mm, F1.7
- Min. Illumination color 0.1Lux, W/B 0.01 Lux
- Optical Zoom 4X
- IR SMT 6 Pcs/ 30M.
- Support PTZ
- Power Supply DC12V, 1A / DC12V, 2A

Specification

Model	HA-394BP202
Image Sensor	1/2.8" SONY IMX 323 CMOS
System	4-in-1 (AHD/CVI/TVI/CVBS)
vari-focal	Support
lens	2.8-12mm, F1.7
Optical Zoom	Support 4X
Semi auto focus	Support
Min. Illumination	color 0.1Lux, W/B 0.01 Lux
IR SMT	6 Pcs/ 30M.
Pan Rotation Range	0°~180°
Tilt Rotation Range	0°~55°
Pan Speed	0.1°~20°/s
Tilt Speed	0.1°~10°/s
Day & Night	auto/ color/ white&black
Electronic Shutter	1/25s ~ 1/10000s
Support	AWB, AGC Adjustable, Exposure Mode (Auto/Manual)
Support	Sharpness, Saturation, Brightness & Contrast Adjustable, automatic exposure, 2D/3D Noise reduction
Support	Image Orientation Mirror/Flip
Support	COC (UTC)
Support	PTZ
Support	Interface BNC input
Support	Bracket Wall & Ceiling Bracket
Power Supply	DC12V, 1A / DC12V, 2A
Work Environment	-20°C~60°C, 10%~90% Humidity
Power consumption	IR ON: Max8.7W / Min. 5.2W.
Power consumption	IR Off : Max.5.8W / Min. 2.2W.
Lightning protection rating	3000V.
Dimension	168mm x 70mm x 87mm (L*W*H)

PTZ CAMERA SERIES
4in1 System

MINI PTZ